

Standard equipment

- Manual emergency lowering device
- Battery charger with automatic switch-off
- Low battery alert
- Battery switch-off
- Inclinometer with cut out and alarm
- Load sensor with audible/visual motion cut out and alarm
- Electrical scissor protection
- Non marking tires
- Cylinder holding valve
- Non-slip deck surface
- Full height access gate with spring-lock
- 2WD traction, DC electric motors
- Electromagnetic brakes on the 2WD
- Swivel caster interlock for straight line driving
- Pothole protection
- Control box on platform IP65, with proportional joystick and emergency stop
- Selector for 3 different proportional speed
- Audible motion alarm
- Horn
- Ground control panel with key switch
- Flashing beacon

Benefits

- ✓ Smooth roller castors with non-marking tyres suitable for soft ground
- ✓ It can be driven through standard doorways and carried in passenger elevators
- ✓ Ease of transport thanks to fork lift, lifting points and several slinging hook points
- ✓ Outstanding battery capacity provides long endurance
- ✓ Safe and reliable emergency lowering device with pull-up handle
- ✓ Digital inclinometer with cut out and audible alarm when exceeding the allowable tilt angle (no stabilisers required)
- ✓ Battery charger can be switched on for long periods, ensuring 100% battery charge
- ✓ Higher productivity thanks to the powered traction also allowed at full height
- ✓ Reduced environmental impact by electric traction
- ✓ Easier loading operation on ramps
- ✓ Excellent manoeuvrability, safe, quick and precise positioning in very congested sites



EASY UP 5 SP

Number of scissors		3
A	mm	3200
B	mm	5200
C	mm	25
D	mm	1810
E	mm	710
Capacity (including 1 person)	kg	200
Electric motor (power pack)	kW	2
Electric drive motors	V/kW	24/1
Battery	V/Ah	2 x 12/105
Battery charger	V	230
Oil tank capacity	l	2
Lifting time	s	17/20
Max side/longitudinal tilt angle	degrees	1.5/2.5
Gradeability	%	25
Traction speed	km/h	0 - 4
Safety traction speed	km/h	0.6
Internal turning radius	m	0
External turning radius	m	1.25
Total weight	kg	500

EASY UP 5 SP

