Concrete Mixers

Standard Equipment

- Three-phase 400V/50 Hz motor or Diesel engine: Lombardini 15LD500 8.1 kW
- Pneumatic wheels and legs adjustable in height
- Water tank with level indicator
- Separate loading of water and aggregates
- ✓ Side protection guards
- ✓ Drum rotation gear guard

Optional Accessories

✓ Scraping shovel with 20 m coiler unit and clutch

 $\begin{tabular}{ll} \textbf{Applications} \\ \textbf{The mixing system with tilting drum makes it possible to mix different} \\ \end{tabular}$ materials like mortars, plasters and concrete.



Scraping shovel and side conveyor



SCRAPING SHOVEL		
Motor power rate	kW	1.5
Running current	Α	4
Electric cable length	m	20
Steel rope length	m	20
Traction speed	m/sec	0.5
Traction capacity	kg	400
Drum speed	rpm	63
Weight	kg	105

		BRO 500
Drum capacity	I	550
Batch output	1	290
Batches/h	n.	30
Water tank capacity	1	65
Motor power rate 400V/50Hz	kW	2.9 (8.1)
Running current	Α	6.4
SPL in operator's position	dB(A)	85
Machine weight	kg	1020
Dimensions w/l/h	mm	1855/2150/3100