

COMBI 200 VA

Water-cooled tile saw - blade Ø 200 mm

Standard Equipment

- ✓ Single-phase 230V/50Hz electric motor, 1.5 kW with thermal protection and minimum voltage coil
- ✓ IP 55 switch
- ✓ IP 67 plug
- ✓ Cutting guide
- ✓ Blade Ø 200 mm for tiles - continuous rim
- ✓ Protractor with large support surface
- ✓ Anodised extruded aluminium cutting surface 240 mm
- ✓ Shatter-resistant plastic tray to contain and recover water
- ✓ Stand

Optional Accessories and recommended blades

- ✓ Side cutting surface
- ✓ Diamond blade Ø 200 mm for tiles - continuous rim
- ✓ Diamond blade SUPER Ø 200 mm for hard gres tiles - continuous rim

Applications

It is the small portable tile saw with lots of power. Lightweight, compact and handy to use, it is ideal for installers. It offers high cutting capacity: the blade is suitable for all types of material to be cut. Cuts (90°) vertically to the support surface or cuts in tilted position between 90° and 45° (depth adjustment is maintained in all positions). Side cutting surface optional to extend cutting by 240 mm, maintaining stability, due to a bracket bolted onto the stand.

115V/60Hz SPH

MOTOR AVAILABLE

✓ **Combi 200 VA**




Rip guide



High cutting capacity



Optional side surface



Direct transmission



Cutting at 45°

COMBI 200 VA

Blade/bore diameter	Ø mm	200/25.4
Cutting length with (w/out) plunging blade	mm	600(500)
Cutting depth 90° 1 pass/2 passes	mm	40/55
Cutting surface dimensions	mm	700x420
Motor power 230V/50Hz/absorption	kW/A	1.5/9.4
Motor speed	rpm	2800
Water pump	-	IP67, flow rate 13 l/min
Water recovery tray capacity	l	28
Machine dimensions	mm	490/900/480
Packing dimensions	mm	500/950/530
Stand dimensions	mm	480/1060/750
Machine weight (with packing)	kg	33.6 (38)
Stand weight	kg	8.6
Optional surface weight (with packing)	kg	2.34 (4.1)
Side surface bracket weight	kg	0.7
SPL in operator's position	dB(A)	86