

# MIX 80

Compact mortar mixer

## Standard Equipment

- ✓ Single-phase 230V/50Hz motor – Gearmotor in oil bath and high performance Poly-V transmission belt
- ✓ Electric safety limit switch
- ✓ Thermal-magnetic switch with IP 55 no-volt coil and IP 67 plug
- ✓ Grid with bag-splitting blade
- ✓ Extendable handles
- ✓ Lifting hooks
- ✓ Additional wheels for easy handling and loading in transport vehicles
- ✓ **I-DUST grid with connection for vacuum cleaner to limit the dust in the surrounding environment**

## Optional Accessories


- ✓ Rubber paddles kit

## Applications

Small size, lightweight and easy loading in small transport vehicles. The I-DUST grid (with connection for vacuum cleaner) limits the dust in the surrounding environment. Ideal for mixing all the products in bags especially where small quantities need to be mixed at each cycle.

### For mixing

- Skim cote
- Waterproofing products
- Cement-based plasters
- Plaster-based plasters
- Lime-based plasters
- Grouts
- Dry-pack
- Cement with aggregates up to 8 mm
- Self-leveling underlayments
- Masonry mortar
- Fiber-reinforced cement
- Fireproofing materials



**I-DUST grid with connection for vacuum cleaner:** limits the dust in the surrounding environment



The planetary mixing system allows considerable material batching time saving.



MIX 80		
Drum capacity	l	80
Mixing performance	l	55
Drum diameter	mm	608
Max grain size	mm	8
Paddle speed	rpm	44
Electric motor power rate 230V/50Hz	kW	1
Running current	A	6.5
SPL in operator's position	dB(A)	70
Machine weight (packing)	Kg	106(120)
Dimensions w/l/h	mm	660/743/1238
Packing dimensions w/l/h	mm	730/1280/930
Max. stackability*		2(h 1860 mm)

(\*) Number of stackable pieces and total height including pallet