

## MINI SCISSOR LIFTS

# Easy UP 5 Picking

INDOOR USE

## STANDARD EQUIPMENT

- 2WD traction, DC electric motors and electromagnetic brakes
- Swivel caster interlock for straight line driving
- Selector for 3 different proportional speed
- Non marking tires
- Double material tray, non-slip, adjustable and fixed
- Double door access gate with spring-lock
- Control box on platform IP65, with proportional joystick and emergency stop
- Ground control panel with key switch
- Inclinator with audible/visual alarm and motion cut out
- Load sensor with audible/visual alarm and motion cut out
- Electrical scissor protection
- Pothole protection
- Audible motion alarm, horn and flashing beacon
- Low battery alert
- Battery charger with automatic switch-off
- Manual emergency lowering device
- Cylinder holding valve

		EASY UP 5 PICKING
Number of scissors		3
A	mm	3200
B	mm	5200
C	mm	25
D	mm	1820
E	mm	710
Platform dimensions	mm	700x620
Material tray dimensions	kW	500x620
Platform capacity (including 1 person)	kg	120
Material tray capacity	kg	80
Total capacity (including 1 person)	kg	200
Electric motor (power pack)	kW	2
Electric drive motors	V/kW	24/1
Battery	V/Ah	2 x 12/105
Battery charger	V	230
Oil tank capacity	Lt.	2
Lifting time	s	17/20
Max side/longitudinal tilt angle	degrees	1,5/2,5
Gradeability	%	25
Traction speed	km/h	0 - 4
Safety traction speed	km/h	0,6
Internal turning radius	m	0
External turning radius	m	1,25
Total weight	kg	585



5,2 m  
working height



Large material tray, non-slip,  
adjustable in 8 positions.

