

C350 IPOWERR

Water-cooled saw with sliding cutting head – blade Ø 350 mm

Standard Equipment

- ✓ Single-phase 230V/50Hz electric motor 2.5 kW
- ✓ IP 55 circuit breaker with no-volt coil
- ✓ IP 67 plug
- ✓ Laser Pointer
- ✓ Blade Ø 350 mm FLEX for bricks/roof tiles/blocks - sectors
- ✓ Large protractor
- ✓ Cutting surface in stainless steel
- ✓ Shatter - resistant plastic tray to contain and recover water
- ✓ Handles and wheels for manual handling and loading on vehicles
- ✓ Folding legs

Optional Accessories and recommended blades

- ✓ Oversized wheels kit
- ✓ Blade Ø 350 mm FLEX for tiles - continuous rim
- ✓ Blade Ø 350 mm PREMIUM for hard gres tiles - continuous rim
- ✓ Blade Ø 350 mm FLEX for bricks/roof tiles/blocks - sectors
- ✓ Blade Ø 350 mm PREMIUM for granite/stone - sectors s. laser

CUTTING LENGTH 120 cm

Applications

High power saw with cutting marble, bricks and stone. It is designed both for building sites and for the installer. It allows installer to cut tiles up to 1200 mm length with plunge cutting. The C350iPower can be also used in building sites to cut blocks up to 250 mm height with two passes. The tilting cutting head allows for high speed in performing special cuts (45° bevel cut without optional cutting accessories).



C350 IPOWERR		
Blade/bore diameter	ø mm	350/25.4
Max. cutting length (plunge cutting)	mm	1050 (1200)
Max. cutting depth, 1/2 runs	mm	120/250
Cutting surface dimensions	mm	1390x696
Work table height	mm	785
Electric power supply	V / Hz	230 / 50 Sph 230 / 60 Sph
Motor power rate	kW	2.5
Motor speed	rpm	2800
Running current	A	15
Water recovery tray capacity	l	40
Machine dimensions w/l/h head down (head up)	mm	60/1746/1410(1535)
Packing dimensions w/l/h	mm	746/1770/1080
Machine weight (packed)	mm	113 (133)
Max. stackability*		2 (h 2400 mm)

(*) Number of stackable pieces and total height including pallet