

Standard Equipment

- ✓ Single-phase 230V/50Hz electric motor, 1.5 kW with thermal protection and minimum voltage coil
- ✓ IP 55 switch
- ✓ IP 67 plug
- ✓ Laser pointer
- ✓ Cutting guide
- ✓ Diamond blade Ø 250 mm PREMIUM for gres hard porcelain - continuous rim
- ✓ Protractor with large support surface
- ✓ Anodised extruded aluminium cutting surface
- ✓ Shatter-resistant plastic tray to contain and recover water
- ✓ Stand with two rubber wheels
- ✓ Side cutting surface
- ✓ Tile locking tool

Optional Accessories and recommended blades

- ✓ Side cutting surface
- ✓ Rip guide
- ✓ Tile locking tool
- ✓ Diamond blade Ø 250 mm PREMIUM for gres hard porcelain - continuous rim
- ✓ Diamond blade Ø 250 mm FLEX for ceramic - continuous rim

Applications

For a quality cut even on large tiles: 300x600 mm, 900x900 mm and over. Max. cutting length 1500 mm.

They offer high cutting capacity: the blade is suitable for all types of material to be cut. Cuts (90°) vertically to the support surface or cuts in tilted position between 90° and 45° (depth adjustment is maintained in all positions).

Side cutting surface allows to extend cutting, maintaining stability, due to a bracket bolted onto the stand. The machine can mount up to 2 side cutting surfaces and is shipped in a box with stand included.



TILE, MASONRY & SLABS SAWS

COMBI 250-1500 VA		
Blade/bore diameter	Ø mm	250/25.4
Cutting length (with/without plunging blade 2 passes)	mm	1430/1530
Cutting depth 1 pass	mm	66
Cutting depth 2 passes	mm	105
Cutting surface dimensions	mm	500x1615
Electric power supply	V / Hz	230 / 50 Sph 230 / 60 Sph 110 / 50 Sph 115 / 60 Sph
Motor power rate	kW	1.5
Motor speed	rpm	2800
Running current 230 V (110/115 V)	A	9.4 (15.4)
Water pump		IP67, flow rate 13 l/min
Water recovery tray capacity	l	55
Machine dimensions	mm	636/1920/619
Packing dimensions	mm	669/1954/654
Stand dimensions	mm	545/1560/750
Machine weight (with packing)	kg	75 (91)
Stand weight	kg	17
Optional surface weight (with packing)	kg	8.0 (8.6)
SPL in operator's position	dB(A)	86
Max. stackability*		3 (h 2190 mm)

(* Number of stackable pieces and total height including pallet)



Handle for long cuts



OFF button incorporated in the handle



Standard protractor



Cutting at 45°



Standard laser pointer