

Standard Equipment

- ✓ Single-phase 230V/50Hz electric motor, 1.5 kW with thermal protection and minimum voltage coil
- ✓ IP 55 switch
- ✓ IP 67 plug
- ✓ Cutting guide
- ✓ Diamond blade Ø 250 mm PREMIUM for hard gres tiles - continuous rim
- ✓ Protractor with large support surface
- ✓ Anodised extruded aluminium cutting surface
- ✓ Shatter-resistant plastic tray to contain and recover water
- ✓ Stand with two rubber wheels

Optional Accessories and recommended blades

- ✓ Side cutting surfaces
- ✓ Rip guide
- ✓ Tile locking tool
- ✓ Diamond blade Ø 250 mm PREMIUM for hard gres tiles - continuous rim
- ✓ Diamond blade Ø 250 mm FLEX for tiles - continuous rim


Applications

It is ideal for cutting ceramic, stone materials, bricks and stone. Lightweight and compact, it ensures maximum cutting precision thanks to its user-friendly structure and the accessories that come with it. It offers high cutting capacity: the blade is suitable for all types of material to be cut. Cuts (90°) vertically to the support surface or cuts in tilted position between 90° and 45° (depth adjustment is maintained in all positions). Side cutting surface optional to extend cutting, maintaining stability, due to a bracket bolted onto the stand.



TILE, MASONRY & SLABS SAWS

| COMBI 250 VA | | |
|--|--------|--|
| Blade/bore diameter | Ø mm | 250/25.4 |
| Cutting length | mm | 785/660 (with/without plunging blade) |
| Cutting depth 1 pass | mm | 66 |
| Cutting depth 2 passes | mm | 105 |
| Cutting surface dimensions | mm | 500x850 |
| Electric power supply | V / Hz | 230 / 50 Sph 230 / 60 Sph 110 / 50 Sph 115 / 60 Sph |
| Motor power rate | kW | 1.5 |
| Motor speed | rpm | 2800 |
| Running current 230 V (110/115 V) | A | 9.4 (15.4) |
| Water pump | | IP67, flow rate 13 l/min |
| Water recovery tray capacity | l | 36 |
| Machine dimensions | mm | 565/1050/480 |
| Packing dimensions | mm | 610/1090/525 |
| Stand dimensions | mm | 545/1060/750 |
| Machine weight (with packing) | kg | 38 (43) |
| Stand weight | kg | 8.8 |
| Optional surface weight (with packing) | kg | 2.6 (4.5) |
| Side surface bracket weight | kg | 0.7 |
| SPL in operator's position | dB(A) | 86 |
| Max. stackability* | | 3 (h 1750 mm) |




High cutting capacity



Optional side surface



Cutting at 45°



Rip guide

(* Number of stackable pieces and total height including pallet)