

Standard Equipment

- ✓ Three-phase 400V/50-60Hz electric motor
- ✓ IP67 plug
- ✓ Frame with 4 steel wheels
- ✓ Upper limit safety device
- ✓ Direct control with 3-pushbutton IP65 1.5-m pendant control
- ✓ Positioning brake
- ✓ Self-braking motor with magnetic device

Optional Accessories

- ✓ 500 kg gantry (ET 500 TF)
- ✓ 1000 kg gantry (ET 1000)
- ✓ Kit rope pulley assembly and trolley attachment system for transformation 500 kg hoist to 1000 kg hoist (ET 500 TF)

Applications

Thanks to their sturdy structure and powerful motor, ET 500 TF and ET 1000 are particularly suitable for heavy duty use on site.



ET 1000

(ET 500 TF) **500 kg**
(ET 1000) **1000 kg**



(ET 500 TF) **20 m/min**
(ET 1000) **10 m/min**



(ET 500 TF) **42 m**
(ET 1000) **21 m**



HOISTS



ET 500 TF

		THREE-PHASE	THREE-PHASE
		ET 500 TF*	ET 1000*
Maximum capacity	kg	500	1000
Av. full load lifting speed	m/min	20	10
Max. working height	m	42	21
Ø steel rope	mm	5	6
Rope length	m	43	43
Electric power supply	V / Hz	400 / 50 Tph 400 / 60 Tph	400 / 50 Tph 400 / 60 Tph
Motor power rate	kW	2.2	2.2
Motor speed	rpm	1320	1320
Running current	A	7	7
Machine weight	kg	71	75
SPL in operator's position	dB(A)	<72 (1.5 m)	<72
Dimensions w/l/h	mm	380/800/410	382/800/410
Packing dimensions w/l/h	mm	380/810/420	400/820/440

*Available only for non-EU Countries