

AIRONE 200 NEO

Hoists with telescopic arm – capacity 200 kg

Standard Equipment

- ✓ Work positioning lever
- ✓ IP67 plug
- ✓ Prearrangement for all IMER supports (gantry excluded)
- ✓ Upper limit safety device
- ✓ Direct control with 3-pushbutton IP65 1-m pendant control
- ✓ Self-braking motor with magnetic device
- ✓ Hoist protection cover

Optional Accessories

- ✓ Scaffold attachment

Applications

The special machine configuration makes it easy to install thanks to better weight distribution for the operator. The raised loading point simplifies the passing of materials through windows. Airone 200 NEO have an extensible arm up to 1100 mm. Maximum capacity remains unchanged for the entire extension so bulky material can be lifted without the risk of striking the structures.



AIRONE 200 NEO		
Maximum capacity	kg	200
Av. full load lifting speed	m/min	19
Max. working height	m	30
Ø steel rope	mm	4
Rope length	m	31
Electric power supply	V / Hz	230 / 50 Sph
Motor power rate	kW	0.75
Motor speed	rpm	1380
Running current	A	7.5
Machine weight	kg	45
SPL in operator's position	db(A)	<72
Dimensions w/l closed (open)/h	mm	330/850(1100)/520
Packing dimensions w/l/h	mm	390/810/590