

ETR 200 NEO

Hoists with telescopic frame – capacity 200 kg

Standard Equipment


- ✓ Work positioning lever
- ✓ IP67 plug
- ✓ Trolley available for use with a gantry
- ✓ Upper limit safety device
- ✓ Direct control with 3-pushbutton IP65 1.5-m pendant control
- ✓ Self-braking motor with magnetic device
- ✓ Bracket can be extended up to 1120 mm
- ✓ Hoist protection cover

Optional Accessories

- ✓ Scaffold attachment

Applications

ETR 200 NEO lets you work with a bracket from 720 mm up to 1120 mm. Maximum capacity remains unchanged for the entire arm extension so bulky materials can be lifted without the risk of striking against the structures. The low noise level allows working without causing noise harmful to the operator's health and bothersome to others.



200 kg



19 m/min



30 m

ETR 200 NEO

Maximum capacity	kg	200
Av. full load lifting speed	m/min	19
Max. working height	m	30
Ø steel rope	mm	4
Rope length	m	31
Electric power supply	V / Hz	230 / 50 Sph 230 / 60 Sph
Motor power rate	kW	0.75
Motor speed	rpm	1380
Running current	A	7.2
Machine weight	kg	45
SPL in operator's position	db(A)	<70
Dimensions w/l closed (open)/h	mm	330/770(1170)/520
Packing dimensions w/l/h	mm	390/810/590